

配管パイプ【1】

SUS304 重量 kg/M(上段)

呼び径		外径 mm	重量 kg/M(上段)															
A	B		1.0	1.2	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	6.6	7.1	8.0
6	1/8	10.5	.237 ○		.336 ○	.423 ○												
8	1/4	13.8	.319 ○	.377 ○	.460 ○	.588 ○		.807 ○										
10	3/8	17.3	.406 ○	.481 ○	.590 ○	.762 ○	.922 ○	1.07 ○										
15	1/2	21.7		.613 ○	.755 ○	.981 ○	1.20 ○	1.40 ○										
20	3/4	27.2		.777 ○	.960 ○	1.26 ○	1.54 ○	1.81 ○										
25	1	34		.980 ○	1.21 ○	1.59 ○	1.96 ○	2.32 ○	2.66 ○	2.99 ○								
32	1 1/4	42.7		1.24 ○	1.54 ○	2.03 ○		2.97 ○	3.42 ○	3.86 ○								
40	1 1/2	48.6		1.42 ○	1.76 ○	2.32 ○		3.41 ○	3.93 ○	4.44 ○								
50	2	60.5			2.20 ○	2.91 ○		4.30 ○	4.97 ○	5.63 ○		6.91 ○	7.54 ○					
65	2 1/2	76.3			2.79 ○	3.70 ○		5.48 ○	6.35 ○	7.20 ○		8.88 ○						
80	3	89.1				4.34 ○		6.43 ○	7.46 ○	8.48 ○		10.5 ○	11.5 ○					
90	3 1/2	101.6				4.96 ○		7.37 ○	8.55 ○	9.72 ○		12.0 ○		14.3 ○				
100	4	114.3				5.59 ○		8.32 ○	9.66 ○	11.0 ○		13.6 ○		16.2 ○				
125	5	139.8						10.2 ○	11.9 ○	13.5 ○		16.8 ○				21.9 ○		
150	6	165.2						12.1 ○	14.1 ○	16.1 ○		20.0 ○		23.8 ○	25.7 ○		28.0 ○	
200	8	216.3						15.9 ○		21.2 ○		26.3 ○		31.4 ○	34.0 ○			
250	10	267.4						19.8 ○	23.0 ○	26.2 ○		32.7 ○		39.1 ○	42.2 ○			
300	12	318.5						23.6 ○		31.3 ○	35.2 ○	39.0 ○		46.7 ○	50.5 ○			
350	14	355.6							35.0 ○			43.7 ○		52.3 ○	56.5 ○			69.3 ○
400	16	406.4							40.1 ○			50.0 ○		59.8 ○	64.7 ○			79.4 ○
450	18	457.2							45.2 ○			56.3 ○		67.4 ○				89.5 ○

定尺 4 M (6 M)