

パンチングメタル

[全品脱脂処理済]

SUS304

表面状態	板厚 t	×	孔径	×	ピッチ P	開孔率 (%)	1000 × 2000		1219 × 2438	
							重量/枚		重量/枚	
BA	0.3	×	φ	×	ジウ	32	3.24	○		
BA	0.4	×	φ	×	ジウ	32	4.32	○		
BA	0.5	×	φ	×	ジウ	32	5.40	○		
BA	0.6	×	φ	×	ジウ	32	6.48	○		
BA	0.8	×	φ	×	ジウ	32	8.62	○		
BA	1.0	×	φ	×	ジウ	32	10.8	○		
BA	1.2	×	φ	×	ジウ	32	12.9	○		
BA	1.5	×	φ	×	ジウ	32	16.2	○		
2B	0.3	×	0.5	×	1.09	19	3.86	○		
2B	0.4	×	0.5	×	1.09	19	5.14	○		
2B	0.6	×	0.8	×	1.55	24.2	7.22	○		
2B	0.5	×	1	×	2	22.6	6.14	○		
2B	0.6	×	1	×	2	22.6	7.36	○		
2B	0.8	×	1	×	2	22.6	9.82	○		
2B	1.0	×	1	×	2	22.6	12.3	○		
BA	0.5	×	1.5	×	3	22.6	6.14	○		
BA	0.8	×	1.5	×	3	22.6	9.82	○		
BA	1.0	×	1.5	×	3	22.6	12.3	○		
BA	1.0	×	2	×	3	40.2	9.48	○		
BA	0.6	×	2	×	3.5	29.6	6.70	○		
BA	0.8	×	2	×	3.5	29.6	8.92	○		
BA	1.0	×	2	×	3.5	29.6	11.2	○		
BA	1.2	×	2	×	3.5	29.6	13.4	○		
BA	1.5	×	2	×	3.5	29.6	16.8	○		
BA	1.0	×	2.5	×	4	35.4	10.2	○		
BA	0.5	×	3	×	4	50.9	3.90	○		
BA	0.8	×	3	×	4	50.9	6.22	○		
BA	1.0	×	3	×	4	50.9	7.78	○		
BA	0.4	×	3	×	5	32.6	4.28	○		
BA	0.5	×	3	×	5	32.6	5.34	○		
BA	0.6	×	3	×	5	32.6	6.42	○		
BA	0.8	×	3	×	5	32.6	8.54	○	12.7	○
BA	1.0	×	3	×	5	32.6	10.7	○	15.9	○
BA	1.2	×	3	×	5	32.6	12.8	○		
BA	1.5	×	3	×	5	32.6	16.0	○		
BA	2.0	×	3	×	5	32.6	21.4	○		
2B	3.0	×	3	×	5	32.6	32.0	○		
BA	1.0	×	4	×	5	58.0	6.70	○		
BA	0.6	×	4	×	7	29.6	6.70	○		
BA	0.8	×	4	×	7	29.6	8.94	○		
BA	1.0	×	4	×	7	29.6	11.2	○		
BA	1.2	×	4	×	7	29.6	13.4	○		
BA	1.5	×	4	×	7	29.6	16.8	○		
BA	2.0	×	4	×	7	29.6	22.4	○		